

<h2 style="text-align: center;">Flanged Breather</h2>	<h2 style="text-align: center;">Identify Data</h2> <p style="text-align: right;">Rev. 3. 05/16</p>													
<p>Our product is designed for a goal-oriented use of the tank valve or the system created a high degree of pressure away.</p> 	<table border="1"> <tr> <td>Product Group</td> <td style="text-align: right;">LG</td> </tr> <tr> <td>Type</td> <td style="text-align: right;">BRV-ELV</td> </tr> </table>	Product Group	LG	Type	BRV-ELV									
Product Group	LG													
Type	BRV-ELV													
	<p>Application Area</p> <p>Oil, chemical, gas and energy plants, containers, highly inflammable and explosive facilities in the system to ensure.</p>													
	<p>General Data</p> <p>Flanged connections built into the system, assembled plate on a device with a quality certificate.</p>													
	<p>Engineering Data</p> <p>Connection Sizes: DN20-DN100 Pressure Grades: 20mBar+100mBar Operating Temperature: -40°C...+120°C</p> <p>Material Quality:</p> <ul style="list-style-type: none"> - Carbon Steel(1.0570) - Stainless Steel (1.4301;1.4404;1.4571) - Other (Aluminium Alloys) 													
<p>Ordering</p> <p>Ordering Code Buildup</p> <p>LG-BRV-ELV-DN10-PN0.1-B</p> <table border="0"> <tr> <td>LG</td> <td>Equipment Group</td> </tr> <tr> <td>BRV-ELV</td> <td>Equipment Type</td> </tr> <tr> <td>DN10</td> <td>Connection Size</td> </tr> <tr> <td>PN0.1</td> <td>Pressure Grade</td> </tr> <tr> <td>1.4571</td> <td>Material Quality</td> </tr> <tr> <td>B</td> <td>Certificate 3.1 and PED</td> </tr> </table>	LG	Equipment Group	BRV-ELV	Equipment Type	DN10	Connection Size	PN0.1	Pressure Grade	1.4571	Material Quality	B	Certificate 3.1 and PED	<p>Certificates</p> <p>EN10204 3.1B certificates, PED 97/23/EG pressure test protocol</p>	
LG	Equipment Group													
BRV-ELV	Equipment Type													
DN10	Connection Size													
PN0.1	Pressure Grade													
1.4571	Material Quality													
B	Certificate 3.1 and PED													